Carousel

Basic Syntax

```
<carousel>
{{:wiki:plugin:bootswrapper:image-placeholder-big.jpg?nolink|}}
{{:wiki:plugin:bootswrapper:image-placeholder-big.jpg?nolink|}}
{{:wiki:plugin:bootswrapper:image-placeholder-big.jpg?nolink|}}
</carousel>
```

OR

```
<carousel>
<slide>{{:wiki:plugin:bootswrapper:image-placeholder-
big.jpg?nolink|}}</slide>
<slide>{{:wiki:plugin:bootswrapper:image-placeholder-
big.jpg?nolink|}}</slide>
<slide>{{:wiki:plugin:bootswrapper:image-placeholder-
big.jpg?nolink|}}</slide>
</carousel>
```

Previous Next

Caption

```
<carousel>
<slide>
{{:wiki:plugin:bootswrapper:image-placeholder-big.jpg?nolink|}}
<caption>
=== First slide label ===
Nulla vitae elit libero, a pharetra augue mollis interdum.
</caption>
</slide>
[...]
</carousel>
```

First slide label

Nulla vitae elit libero, a pharetra augue mollis interdum.



Second slide label

Lorem ipsum dolor sit amet, consectetur adipiscing elit.



Third slide label

Praesent commodo cursus magna, vel scelerisque nisl consectetur.

Previous Next

Attributes

Attibute	Type	Default Value	Description
`interval`	number	`5000`	The amount of time to delay between automatically cycling an item. If false, carousel will not automatically cycle.
`pause`	string	`hover`	Pauses the cycling of the carousel on mouseenter and resumes the cycling of the carousel on mouseleave.
`wrap`	boolean	`true`	Whether the carousel should cycle continuously or have hard stops.
`keyboard`	boolean	`true`	Whether the carousel should react to keyboard events.

From:
https://wiki.ph-freiburg.de/!handbuch/ - **PH Freiburg**

Permanent link:
https://wiki.ph-freiburg.de/!handbuch/plugins:bootswrap:carousel

Last update: **14.05.2024 17:10**